



Nothing is the way it seems...



... and nothing will ever be the same again! Break down the door to a new world of graphics with the Mystify 5950 Ultra. Conjure up a level of ultrarealism that will more than convince you with its speed and stability. Experience your games with absolutely realistic graphics and movie-quality effects that will take your breath away.

Solid graphics power and performance reserves with an optimized, whisper-quiet cooling system that will quicken the pulse of any tuning fan: that's what the Mystify 5950 Ultra is all about. With 256 MB 256-bit DDR RAM, genuine 950 MHz and a memory bandwidth of 30.4 Gbps. The Cine FX™ 2.0 engine, Intellisample™ HCT, UltraShadow™ technology and full Direct X® 9.0 and OpenGL® 1.5 support guarantee first-class graphics quality with perfect rendering, an impressive interplay of light and shadow and lifelike textures. So close to reality — Ultra Realism.

Splinter Cell™, Warcraft® III and Gun Metal™: With these three games, we have created a varied pack guaranteed to enthrall you and allow you to test out the fantastic possibilities of the Mystify 5950 Ultra to the limit.

MYSTIFY YOUR GAMES

Want to squeeze every last drop of performance from your hardware? Push the possibilities of your games to the limit? Then pay attention to this label: "MYSTIFY YOUR GAMES". Experience perfectly tuned professional equipment, specially developed for the needs of demanding players.



Technical data

Chipset

- nVIDIA GeForce FX 5950 Ultra multi-display GPU
- Graphics chip Clock frequency: 475 MHz
- Memory speed: 950 MHz (DDR)
- Fill rate (AA samples/sec): 3,8 billion
- Polygons/sec.: 356 million
- Memory bandwidth: 30,4 GB/sec.
- Memory: 256 MB DDR (256 bit)

Interface

- AGP 3.0 8X compatible
- AGP 8X/4X/2X and AGP texturing supported

Features

- CineFX Shading architecture
- High-resolution 3D Rendering Engine
- Intellisample technology with Hi-Res Compression Technology (HCT)
- UltraShadow technology
- Dual 400 MHz RAMDACs with resolution of up to 2048 x 1536 at 85 Hz

Memory interface

- 256 MB DDR SGRAM (256 bit)

Connections

- TV/Video input/video output
 - Integrated TV encoder
 - Supports S-video TV In/Out
 - NTSC or PAL digital in/output
 - Support for external digital TV
- DVI-I
 - Integrated dual-channel TMDS transmitter
 - Support for up to 1280 x 1024 screen resolution

Miscellaneous

- Highest quality and performance with Microsoft® and Windows® XP support
- Unified Driver Architecture (UDA)
- Complete OpenGL® 1.5 and OpenGL support
- Microsoft DirectX® 9.x optimization and support

System requirements

- Intel® Pentium 4/III/II Celeron, AMD® K7/K6 and/or compatible with AGP 2X or AGP 2X/4X/8X universal slot
- Motherboard must meet AGP specifications
- VGA/super VGA monitor, minimum resolution support of 640 x 480 required
- 32 MB or more RAM memory recommended
- CD-ROM drive
- Minimum 300 watts
- A free power connection to the power supply
- One free AGP and PCI slot
- One free internal power connector

Art.No.: 7340

EAN-Code: 4017273673400

Warranty: 24 months